

II. AMENDMENTS TO THE CLAIMS

The listing of claims that follows is complete and replaces any previous listing of claims.

What is claimed is:

1. (Currently amended) A system for testing an overhead traveling vehicle, the system comprising:

a test fixture for supporting the overhead traveling vehicle in a stationary state during analysis testing, the test fixture including a rotatable bearing set for rotatably engaging an outside edge of a wheel of the overhead traveling vehicle during testing such that the overhead traveling vehicle hangs from the test fixture; and

a data collector for collecting data regarding an operation parameter of the overhead traveling vehicle.

2. (Original) The system of claim 1, wherein the rotatable bearing set is mounted to a rail.

3. (Original) The system of claim 2, wherein the rail is C-shaped, and the rotatable bearing set is positioned in a first extremity of the rail.

4. (Original) The system of claim 3, wherein the rail further includes an opening in a second extremity thereof over the bearing set.

Serial No. 10/669,849

2/9

5. (Original) The system of claim 4, wherein the data collector includes one of a handheld tachometer and a handheld optical sensor, positionable in the opening to observe the wheel.
6. (Original) The system of claim 1, wherein the data collector further comprises a data analyzer for analyzing the operation parameter of the overhead traveling vehicle.
7. (Original) The system of claim 6, wherein the test fixture further includes a reflective section and the overhead traveling vehicle includes an optical sensor for interaction with the reflective section, and wherein the operation parameter includes a reading of the optical sensor.
8. (Original) The system of claim 1, wherein the test fixture further includes a reflective section and the overhead traveling vehicle includes at least one optical sensor for use with the reflective section.
9. (Original) The system of claim 8, wherein the operation parameter includes a reading of the optical sensor.

10. (Currently amended) A test fixture for supporting an overhead traveling vehicle for testing, the test fixture comprising:

a rotatable bearing set for rotatably engaging an outside edge of a wheel of the overhead traveling vehicle such that the wheel can rotate but the overhead traveling vehicle remains stationary; and

a raised support for supporting the rotatable bearing set,

wherein the raised support includes a C-shaped rail,

and wherein the rotatable bearing set is mounted in a lower extremity of the C-shaped rail.

11. (Currently amended) The test fixture of claim 10, ~~wherein the raised support includes a rail, and~~ the rotatable bearing set is mounted in an opening in the C-shaped rail.

12. (Cancelled)

13. (Currently amended) The test fixture of claim ~~12~~ 11, wherein the C-shaped rail further includes an opening in an upper extremity thereof over the rotatable bearing set for a data collector.

14. (Original) The test fixture of claim 10, further comprising a reflective section on the rail for interaction with an optical sensor of the overhead traveling vehicle.

Serial No. 10/669,849

4/9

15. (Original) The test fixture of claim 14, wherein the reflective section includes a plurality of tape lanes, each lane for interaction with a different optical sensor of the overhead traveling vehicle.

16. (Currently amended) A method of calibrating an overhead traveling vehicle, the method comprising:

supporting the overhead traveling vehicle on a test fixture, in a stationary state, by rotatably supporting an outside edge of each wheel of the overhead traveling vehicle with a rotatable bearing set including a pair of rotatable bearings such that the overhead traveling vehicle hangs from the test fixture;

operating a portion of the overhead traveling vehicle; and

adjusting a control of the overhead traveling vehicle to calibrate the overhead traveling vehicle.

17. (Original) The method of claim 16; wherein the test fixture includes a rail substantially similar to that which the overhead traveling vehicle is configured to operate on.

18. (Original) The method of claim 16; wherein the test fixture includes a reflective section for interaction with an optical sensor of the overhead traveling vehicle, and wherein the operating step includes activating the optical sensor and the adjusting step includes adjusting a control of the optical sensor.

19. (Original) The method of claim 16; wherein the operating step includes driving each

Serial No. 10/669,849

5/9

wheel with a respective servomotor, and the adjusting step includes adjusting at least one servomotor control.

20. (Original) The method of claim 16; wherein the adjusting step includes calibrating the overhead traveling vehicle to have an operation parameter that substantially matches that of a replaced overhead traveling vehicle.

Serial No. 10/669,849

6/9